



The Effect of Reservoir Pressure Depletion on Well Productivity in Fractured Reservoirs

Kadeethum, Teeratorn; Salimzadeh, Saeed; Nick, Hamid M.

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Kadeethum, T., Salimzadeh, S., & Nick, H. M. (2017). *The Effect of Reservoir Pressure Depletion on Well Productivity in Fractured Reservoirs*. Abstract from Danish Hydrocarbon Research and Technology Centre Technology Conference 2017, Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

The Effect of Reservoir Pressure Depletion on Well Productivity in Fractured Reservoirs

Teeratrorn Kadeethum, Saeed Salimzadeh, Hamid M. Nick

Danish Hydrocarbon Research and Technology Centre, Technical University of Denmark, Lyngby, Denmark

Many production wells in North Sea reservoirs suffer from intense productivity reduction during primary production. These reservoirs are naturally fractured reservoirs; hence, fractures probably take main responsibilities for this decline. During a primary recovery, pressure-depletion increases effective stresses; and increases contact stresses on the fracture surfaces, subsequently reduces a fracture aperture and the fracture hydraulic conductivity. The objective of this study is to investigate the extent of mechanical effects on the fracture closure and corresponding productivity reduction. Flow through fractures are modelled using the cubic law, the fracture stiffness is captured using both linear and classic Barton-Bandis model. The equations are solved both analytically (for simple geometry) and numerically using the finite element code, CSMP (see Figure 1). The production history of a well in the North Sea has been used for benchmarking, and sensitivity analysis is performed to understand the effect of each parameter on the productivity reduction as well as interactions between each variable.




Figure 1 Steady-state production comparison between analytical and numerical solutions